

SMART WiFi RELAY MECH

Make your lighting or switches Smart







Smartify your on/off switch to allow remote operation from anywhere

- · Make your on/off switch or exhaust fan smart by converting your current switch to our Smart relay module
- · Fits conveniently into the existing switch plate
- · Perfect for new or retro-fit installations
- Slots seamlessly into HPM® HPM Excel Life®, Clipsal® and Vynco® branded ٠ wall plates
- · Control from anywhere via app or voice control
- · Build schedules and timing to automate your home
- · Create virtual automation looping without the hassle of installing long cable runs*
- · Soft start for improved lamp life
- Connects to other BrilliantSmart devices and other ٠ compatible products
- · Overheat and over-current protection
- · Manual push button is in perfect sync with app
- * Virtual automation requires some automation scenes to be programmed in app

APPLICATIONS

works with the

Google Assistant

- · Connects to any lighting/switch indoor only
- · Group lights, so they can be switched on or off at the one time
- Create scenes using IFTTT, so lights come on based on certain behaviour, ie: when movement is detected via a sensor, the lights turn on automatically

BRILLIANT SMART SMART RELAY SWITCH MECH 21322

LED, SI

VORKS WITH

alexa



D

Works with

IFTTT

Brilliant

SMART WiFi RELAY MECH


TECHNICAL SPECIFICATIONS


| Operating Voltage: | 240V / 50Hz | | | | | |
|------------------------|--|--|--|--|--|--|
| Class: | Class II (2) | | | | | |
| Maximum Load: | 300W LED / 500W incandescent / 50W motor (exhaust fan) | | | | | |
| Minimum Load: | 2W or 0.33μ F X2 capacitor | | | | | |
| Operating Temperature: | 10°C - 30°C | | | | | |
| Protection Type: | Over heat & over current | | | | | |
| Control Type: | Push button / BrilliantSmart app Soft start for improved lamp life | | | | | |
| Connection Terminals: | 3 x 3mm diameter (7mm ²) screw | | | | | |
| Material: | Flame retardant ABS for housing | | | | | |
| LED Indicator: | Blue | | | | | |
| Plate Compatibility: | Slots seamlessly into HPM [®] , Clipsal [®] and Vynco [®] branded wall plates with multiple button head shapes (series 30 type) | | | | | |
| Warranty: | 1 year replacement | | | | | |
| WiFi Info: | IEEE802.11b/g/n, 2.4GHz Mac Encryption; WEP/WAPI/TKIP/AES | | | | | |
| Device Requirements: | iOS 8.0 or higher, Android 4.1 or higher | | | | | |
| Standards: | AS/NZS 60669-2-1 IEC 60669-1 | | | | | |
| | | | | | | |


INSTALLATION

Must be installed by a licensed electrician









| | MODEL | COLOUR | DESCRIPTION | BOX SIZE | GROSS WEIGHT | BOX QTY | BARCODE/TUN |
|---------------|-------|--------|---------------------------------|--------------------------|--------------|---------|---------------------|
| RETAIL BOX | 21322 | White | Smart WiFi Relay Mech | W70 x H110 x D29.5 mm | 0.05 kg | 1 pc | 9 "312641"213222" > |
| INNER CTN | 21322 | White | Smart WiFi Relay Mech SRT | W155 x H57 x D57 mm | 0.45 kg | 10 pc | 19312641213229 |
| OUTER CTN | 21322 | White | Smart WiFi Relay Mech | W320 x H185 x D180 mm | 1.30 kg | 20 pc | 29312641213226 |