CAW & CCW SERIES

The CCW and CAW series of connectors have been specially designed to provide a waterproof connection between insulated overhead services to a variety of bare overhead mains. Both single and double tap models are available.



Product Number	Mains Range			Service Taps		Pack			
	Stranding	Area (mm²)	OD (mm)	Range (mm²)	Quantity	Size (pcs)			
Connectors for Bare Copper Mains									
CCW35	7/1.00 to 19/3.00 Cu	5.5 to 135	3 to 15	6 to 35	1	12			
CCW235	7/1.00 to 19/3.00 Cu	5.5 to 135	3 to 15	6 to 35	2	12			

CCW35E

CCW235

CCW SERIES

Mains: Bare copper

Service: Insulated copper or aluminium

- + Piercing connector on service tap
- + Complies with relevant sections of AS4396
- + Disconnection of service by easy removal of the connector from the mains
- + Two tap (CCW235) model available

INSTALLATION NOTES

Use only a 13mm AF, six point hexagon socket to tighten bolts.

All other connections made on the service and consumers cable must also be waterproof to prevent moisture ingress through the cable into the connector.





Product Number	Mains Range			Service Taps		Pack			
	Stranding	Area (mm²)	OD (mm)	Range (mm²)	Quantity	Size (pcs)			
Connectors for Bare Aluminium Mains									
CAW35	7/1.75 to 19/3.75 Al	16 to 210	5 to 19	6 to 35	1	12			
CAW235	7/1.75 to 19/3.75 AI	16 to 210	5 to 19	6 to 35	2	12			

CAW35E

CAW235

CAW SERIES

Mains: Bare aluminium

Service: Insulated copper or aluminium

- + Piercing connector on service tap
- + Complies with relevant sections of AS4396
- + Disconnection of service by easy removal of the connector from the mains
- + Two tap (CAW235) model available
- + Simple M8 socket operation

INSTALLATION NOTES

Use only a 13mm AF, six point hexagon socket to tighten bolts.

All other connections made on the service and consumers cable must also be waterproof to prevent moisture ingress through the cable into the connector.

PLEASE NOTE: The products on this page can be ordered with high visibility shear-off identification tags. To order the products with these identification tages please add the suffix E to the end of the product number when ordering.



Recommended tool for all products: RPS13/17-6H or RPS13/17-6SH

