3015/4XXUA-VW

Clipsal Iconic - 4 switched sockets - 2 gangs - 10 A - vivid white



Main

Range	Clipsal Iconic		
Product or component type	Switched socket		
Device presentation	Complete product		
Outlet poles configuration	2P + E with shutter		
Type of packing	Polybag		
Quantity per set	Set of 1		
Sale per indivisible quantity	1		
Rated current	10 A, 250 V AC, 50 Hz		

Complementary

oompiomontal y			
Device mounting	Flush		
Number of power socket outlets	4		
Number of rocker	4		
Outlet standard	Australian		
Outlet standard description	With earthing contact		
Outlet standard	Australian/New Zealand		
Ground lug position	Straight 180° position		
Fixing mode	By screw		
Installation direction	Horizontal		
Colour tint	Vivid white (VW)		
Surface finish	Matt		
Ambient air temperature for operation	045 °C		
Relative humidity	1095 %		
Electrical durability	12000 cycles		
Connections - terminals	3 x screw terminals		
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)		
Clamping connection capacity	1 x 2.54 x 2.5 mm² (rigid) 1 x 2.54 x 2.5 mm² (stranded) 1 x 2.54 x 2.5 mm² (flexible)		
Wire stripping length	16 mm		
Material	ABS (acrylonitrile butadiene-styrene) for cover frame POM (polyoxymethylene) for shutter POM (polyoxymethylene) for shutter POM (polyoxymethylene) for locking bar PC (polycarbonate) for fixing frame PP (polypropylene) for rocker PC (polycarbonate) for cover frame		
Height	214 mm		
Width	78 mm		
Depth	32 mm		
Embedding depth	18 mm		
Product weight	0.216 kg		
Standards	AS/NZS 3112		

Environment

_		
product certifications	RCM	