

Product data sheet Characteristics

3025CSG

Connected Socket, Iconic, BLE default mode, Twin horizontal, 10 A, 240 V, Grid





Main

mani	
Range compatibility	Wiser mounting bracket Wall box
Product brand	Clipsal
Range	Iconic
Product or component type	Connected switched socket
Outlet poles configuration	2P + E

Complementary

Device presentation	Mechanism with fixing frame	
Device mounting	Flush	
Socket-outlet type	Twin switched socket-outlet	
Socket number	2	
Outlet standard	Australian	
Rated current	10 A	
[Ue] rated operational voltage	240 V AC 50 Hz	
Colour tint	White	
Surface finish	Matt	
Local signalling	LED	
Control type	Rocker on/off switching By mobile application	
Software name	Wiser by SE App	
Communication network type	Wireless Zigbee (24052480 MHz), 10 mW at < 50 m	
Memory description	Backup memory - date and time for 6 h Backup memory - program for indefinite period	
Material	Plastic	
Type of installation	Indoor installation	

Environment

IP degree of protection	IP20	
Relative humidity	590 % non-condensing	
Standards	AS/NZS 3112 safety AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	202.0 g	
Package 1 Height	5.4 cm	
Package 1 width	9.5 cm	
Package 1 Length	14.1 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	