

Product data sheet

Characteristics

3025RCD30-VW

Clipsal Iconic, switched socket, 2 switch & 2 socket, vert, RCD, 10 A, Vv White



Main

| | |
|----------------------------|---------------------|
| Range | Clipsal Iconic |
| Product or component type | Switched socket |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E with shutter |
| Outlet standard | Australian |

Complementary

| | |
|--------------------------------|--|
| Device mounting | Flush |
| Number of power socket outlets | 2 |
| Number of rocker | 2 |
| Range compatibility | Clipsal Iconic |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Ground lug position | Straight 180° position |
| Device composition | 1 residual current device (RCD) 30 mA |
| Fixing mode | By screw |
| Installation direction | Horizontal |
| Colour | Vivid white (VW) |
| Surface finish | Matt |
| Type of packing | Polybag |
| Quantity per set | Set of 4 |
| Sale per indivisible quantity | 1 |
| Rated current | 10 A at 250 V AC 50 Hz |
| Electrical durability | 12000 cycles |
| Screwdriver shape | Square drive no 1 (SQ1) Philips No 2 |
| Clamping connection capacity | 1 x 2.5...4 x 2.5 mm ² for stranded cable(s) 1 x 2.5...4 x 2.5 mm ² for flexible cable(s) 1 x 2.5...4 x 2.5 mm ² for rigid cable(s) |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate): cover frame ABS (acrylonitrile butadiene-styrene): cover frame PC (polycarbonate): fixing frame PP (polypropylene): rocker POM (polyoxymethylene): shutter |
| Height | 78 mm |
| Width | 120 mm |
| Depth | 42 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient air temperature for storage | 0...60 °C |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Standards | AS/NZS 3112 AS/NZS 3190 |
| Product certifications | RCM |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 110.0 g |
| Package 1 Height | 15.2 cm |
| Package 1 width | 7.8 cm |
| Package 1 Length | 12 cm |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 25 |
| Package 2 Weight | 2.75 kg |
| Package 2 Height | 33.5 cm |
| Package 2 width | 26.1 cm |
| Package 2 Length | 33.5 cm |
| Unit Type of Package 3 | BB1 |
| Number of Units in Package 3 | 5 |
| Package 3 Weight | 1.046 kg |
| Package 3 Height | 10.6 cm |
| Package 3 width | 14.8 cm |
| Package 3 Length | 22 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |