

Product data sheet

Characteristics

3043USBG

Clipsal Iconic, 3 USB Charger, Type A, 2.1 A, 240 V



Main

Range	Clipsal Iconic
Product or component type	USB charger
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	3 USB 2.0 type A 5 V DC, maximum load current: 2.1 A
Maximum load current with 2 outputs used simultaneously	4.5 A

Complementary

Device mounting	Flush
Device presentation	Mechanism with fixing frame
Colour tint	Vivid white
Surface finish	Matt Textured
Fixing mode	By screws
Type of packing	Polybag
Sale per indivisible quantity	1
Ambient air temperature for operation	0...35 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	5...90 %
Protection type	Short time short-circuit protection
Number of terminals	3 screw terminal
Screwdriver shape	Philips No 2 Square drive no 1 (SQ1)
Clamping connection capacity	4 x 2.5 mm ² for stranded cable(s) 4 x 2.5 mm ² for flexible cable(s) 4 x 2.5 mm ² for rigid cable(s)
Wire stripping length	10 mm
Height	71 mm
Width	115 mm
Depth	5 mm
Embedding depth	35 mm

Environment

Product certifications	RCM
------------------------	-----

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	123.0 g
Package 1 Height	4 cm
Package 1 width	7.1 cm
Package 1 Length	11.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.25 kg
Package 2 Height	32.8 cm
Package 2 width	10.2 cm
Package 2 Length	14.65 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	6.2 kg
Package 3 Height	33.5 cm
Package 3 width	26.1 cm
Package 3 Length	33.5 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile