# Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications





# Toggle adaptor, Clipsal Solis T Series, for switch mechanism, brushed brass

40TA-BB

# Main

Range	Clipsal Solis T Series	
Product or component type	Adaptor	
Outlet standard deviation	Australian/New Zealand	

# Complementary

Device mounting	Flush
Control type	Toggle switch
fixing mode	Click-in
Colour tint	Brushed brass
Installation direction	Horizontal
Surface finish	Aluminium
surface treatment	Metallic
Number Of Switches	1
Material	Aluminium
Height	51 mm
Width	22 mm
Depth	30 mm
Product certifications	RCM

# **Environment**

Ambient air temperature for operation	045 °C
Relative humidity	1095 %

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	7.5 cm
Package 1 Length	7.5 cm
Package 1 Weight	37 g
Unit Type of Package 2	BB1
Number of Units in Package 2	4

Package 2 Height	15.5 cm
Package 2 Width	8 cm
Package 2 Length	8 cm
Package 2 Weight	218 g
Unit Type of Package 3	CAR
Number of Units in Package 3	120
Package 3 Height	34 cm
Package 3 Width	36 cm
Package 3 Length	48 cm
Package 3 Weight	4.524 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint		
Total lifecycle Carbon footprint	10	

## **Use Better**

EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
Use ∆gain	

### Use Again

○ Repack and remanufacture		
Take-back	No	

40TA-BB

Image of product / Alternate images

**Alternative** 



























