



Main

Range	Clipsal Iconic
Product or component type	Electronic switch
Device presentation	Mechanism

Complementary

Device mounting	Flush
Actuator	Push-button
Fixing mode	Clip-in
Colour tint	Vivid white
Surface finish	Glossy
Type of packing	Box
Sale per indivisible quantity	1
Time delay	1...86400 s (24 h) adjustable
Remote control type	Push-button Wiser room application
[Ie] rated operational current	10 A
[Ue] rated operational voltage	220...240 V AC 50 Hz
Load type	LED lighting 10 A Incandescent lamp 10 A Low voltage halogen lamp with iron core transformer 10 A Low voltage halogen lamp with electronic transformer 10 A Fluorescent lamp 10 A Compact fluorescent lamp 10 A Resistive 15 A
Power range	> 0 W
Derating factor	Number of devices 1 10 A without derating Number of devices 2 7.5 A with derating factor Number of devices 3 6.5 A with derating factor Number of devices 4 with derating factor Number of devices 5 with derating factor Number of devices 6 with derating factor
Operating distance	30 m
Control signal type	Controllink
Connections - terminals	Screw terminals
Number of terminals	4
Wiring configuration	3 wires with neutral
Screwdriver shape	Philips Square drive no 1 (SQ1)
Local signalling	LED indicator warm white
Material	PC (UL94 V-2) for top PC MAS056 (UL94 V-2) for bottom
Height	24 mm
Width	48 mm
Depth	56 mm
Embedding depth	52 mm
Standards	AS/NZS 60669.2.1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

ambient air temperature for storage	0...60 °C
ambient air temperature for operation	0...45 °C
relative humidity	0...90 %
