

Product data sheet Characteristics

438-TR SOCKET CORD EXTENSION 0.75X1SQ FLEXIBLE 250V



Main Range of product Standard Series Product or component Socket-outlet type Colour Transparent Product brand Clipsal Quantity per set Set of 1 Cover type Complete housing

Complementary

Marking Without marking Local signalling Without light indicator Material PVC (polyvinyl chloride) [In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm Diameter 43 mm	Colour code	TR	
Material PVC (polyvinyl chloride) [In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm	Marking	Without marking	
[In] rated current 10 A [Ue] rated operational voltage 250 V AC Depth 71 mm	Local signalling	Without light indicator	
[Ue] rated operational voltage 250 V AC Depth 71 mm	Material	PVC (polyvinyl chloride)	
Depth 71 mm	[In] rated current	10 A	
	[Ue] rated operational voltage	250 V AC	
Diameter 43 mm	Depth	71 mm	
	Diameter	43 mm	

Environment

	Ý
AS/NZS 3112	
AS 3100	į
AS 3109	
AS/NZS 3122:approval number S/1	
	AS 3100 AS 3109

Packing Units

PCE	
1	
0.057 kg	
7.2 cm	
5 cm	
5 cm	
	1 0.057 kg 7.2 cm 5 cm