

### Product data sheet Characteristics

# 56C310-CG

## 56 Series switched socket surface IP66 3 pin 10 A - Charcoal Grey





#### Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Chemical grey

#### Complementary

Number of poles	3
Plug, socket category	Low voltage
Outlet standard	Australian/New Zealand
Plug, socket, control station shape	Straight
Number of modules	1
Number of power socket outlets	1 protective cover
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC 50 Hz
Poles description	1P + N + E
Protection type	Without protection
Device mounting	Surface
Material	ABS (acrylonitrile butadiene-styrene): cover
Contacts material	Pins: phosphor bronze
Connections - terminals	Screw terminals cable(s) 1.56 mm²
Electrical connection	Industrial connector
Depth	83 mm
Width	101 mm
Height	204 mm
Targeted country	Australia

#### Environment

Standards	AS/NZS 3133 AS/NZS 3123
Ambient air temperature for operation	-2575 °C
IP degree of protection	IP66 conforming to AS 60529

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.72 kg
Package 1 Height	83 mm
Package 1 width	101 mm
Package 1 Length	204 mm

#### Offer Sustainability

Sustainable offer status	Green Premium product	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	<sup>™</sup> China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	