

Product data sheet Characteristics

56C310LE-GY

56 Series Socket Outlet - 10A - 3 Pin - 1P -250V - Less Enclosure - Grey





Main

TTT COLUMN	
Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Grey (RAL 7035)

Complementary

Number of poles	3
Plug, socket category	Low voltage
Outlet standard	Australian/New Zealand
Plug, socket, control station shape	Straight
Number of modules	1
Number of power socket outlets	1 protective cover
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC 50 Hz
Poles description	1P + N + E
Protection type	Without protection
Device mounting	Surface
Material	Polycarbonate: cover
Contacts material	Pins: phosphor bronze
Connections - terminals	Screw terminals cable(s) 1.56 mm²
Electrical connection	Industrial connector
Depth	45 mm
Width	101 mm
Height	198 mm
Targeted country	Australia

Environment

Standards	AS/NZS 3133 AS/NZS 3123	
Ambient air temperature for operation	-2575 °C	
IP degree of protection	IP66 conforming to AS 60529	

Packing Units

Package 1 Length	198.000 mm	
Package 1 width	101.000 mm	
Package 1 Height	45.000 mm	
Package 1 Weight	0.400 kg	

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Life Is On