

## Product data sheet

### Characteristics

## 56C315RC-GY

56 Series switched socket surface IP66 RCD 3 pin 15 A - Grey



### Main

|                           |                                            |
|---------------------------|--------------------------------------------|
| Range of product          | Series 56                                  |
| Range                     | Clipsal - 56 Series                        |
| Product brand             | Clipsal                                    |
| Product or component type | Socket-outlet with residual current device |
| Device application        | Power supply                               |
| Colour                    | Grey (RAL 7035)                            |

### Complementary

|                                |                                                |
|--------------------------------|------------------------------------------------|
| Number of poles                | 3                                              |
| Control type                   | Push-button                                    |
| Number of power socket outlets | 1 protective cover                             |
| [In] rated current             | 15 A                                           |
| [Ue] rated operational voltage | 250 V AC 50 Hz                                 |
| Network number of phases       | 1 phase                                        |
| Number of gangs                | 2 gangs                                        |
| Installation direction         | Vertical                                       |
| Device mounting                | Surface                                        |
| Material                       | Polycarbonate                                  |
| Connections - terminals        | Screw terminals cable(s) 1...6 mm <sup>2</sup> |
| Depth                          | 102 mm                                         |
| Width                          | 101 mm                                         |
| Height                         | 204 mm                                         |
| Net weight                     | 0.96 kg                                        |
| Targeted country               | Australia                                      |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Ambient air temperature for operation | -25...75 °C |
| IP degree of protection               | IP66        |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 1.006 kg |
| Package 1 Height             | 11.6 cm  |
| Package 1 width              | 10.8 cm  |
| Package 1 Length             | 20.8 cm  |

Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                             |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |