

Product data sheet Characteristics

56C520-RW

56 Series switched socket surface IP66 5 pin 20 A - Resistance White



Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	White (RAL 9003)

Complementary

Number of poles	5	
Plug, socket category	Low voltage	
Outlet standard	Australian/New Zealand	
Plug, socket, control station shape	Straight	
Number of modules	3	
Number of power socket outlets	1 protective cover	
[In] rated current	20 A	
[Ue] rated operational voltage	500 V AC 50 Hz	
Poles description	3P + N + E	
Protection type	Without protection	
Device mounting	Surface	
Material	PC + PET: cover	
Contacts material	Pins: phosphor bronze	
Connections - terminals	Screw terminals cable(s) 2.56 mm²	
Electrical connection	Industrial connector	
Depth	108 mm	
Width	101 mm	
Height	204 mm	
Targeted country	Australia	

Environment

IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Standards	AS/NZS 3133 AS/NZS 3123

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1074.5 g	
Package 1 Height	118 mm	
Package 1 width	108 mm	
Package 1 Length	210 mm	

Offer Sustainability

EU RoHS Directive	Under investigation	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	