



### Main

|                           |                     |
|---------------------------|---------------------|
| Range of product          | Series 56           |
| Range                     | Clipsal - 56 Series |
| Product brand             | Clipsal             |
| Product or component type | Socket              |
| Device application        | Power supply        |
| Colour                    | Orange (RAL 2004)   |

### Complementary

|                                     |   |
|-------------------------------------|---|
| Plug, socket category               | Low voltage                             |
| Plug, socket, control station shape | Straight                                |
| Mounting mode                       | External mounting                       |
| [In] rated current                  | 20 A                                    |
| [Ue] rated operational voltage      | 500 V AC 50 Hz conforming to EN 60309-2 |
| Poles description                   | 3P + E                                  |
| Voltage colour                      | Black                                   |
| Duration                            | 7 h                                     |
| Material                            | Polycarbonate: housing                  |
| Contacts material                   | Sleeves: brass                          |
| Connections - terminals             | Screw terminals 1...6 mm <sup>2</sup>   |
| Connections - terminals             | Screw terminal                          |
| Socket number                       | 1                                       |
| Socket-outlet type                  | L                                       |
| Outlet standard                     | Industrial                              |
| Cable outer diameter                | 7...16 mm                               |
| Cable entry                         | Cable gland                             |
| Thread type                         | M25                                     |
| Product weight                      | 0.264 kg                                |
| Depth                               | 173 mm                                  |
| Length                              | 173 mm                                  |
| Width                               | 90 mm                                   |
| Height                              | 90 mm                                   |
| Targeted country                    | Australia                               |

### Environment

|                                       |                             |
|---------------------------------------|-----------------------------|
| IP degree of protection               | IP66 conforming to AS 60529 |
| Ambient air temperature for operation | -25...75 °C                 |
| Standards                             | AS/NZS 3120                 |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | No need of specific recycling operations      |