

## Product data sheet Characteristics

# 56CSC520-EO

56 Series Socket Connector - 5 Pin - 20A -500V





#### Main

| Range of product          | Series 56           |
|---------------------------|---------------------|
| Range                     | Clipsal - 56 Series |
| Product brand             | Clipsal             |
| Product or component type | Socket              |
| Device application        | Power supply        |
| Colour                    | Orange (RAL 2004)   |
|                           |                     |

#### Complementary

| I J                                 |   |
|-------------------------------------|---|
| Plug, socket category               | Low voltage                             |
| Plug, socket, control station shape | Straight                                |
| Mounting mode                       | External mounting                       |
| [ln] rated current                  | 20 A                                    |
| [Ue] rated operational voltage      | 500 V AC 50 Hz conforming to EN 60309-2 |
| Poles description                   | 3P + N + E                              |
| Voltage colour                      | Black                                   |
| Duration                            | 7 h                                     |
| Material                            | Polycarbonate: housing                  |
| Contacts material                   | Sleeves: brass                          |
| Connections - terminals             | Screw terminals 16 mm²                  |
| Connections - terminals             | Screw terminal                          |
| Socket number                       | 1                                       |
| Socket-outlet type                  | R                                       |
| Outlet standard                     | Industrial                              |
| Cable outer diameter                | 716 mm                                  |
| Cable entry                         | Cable gland                             |
| Thread type                         | M25                                     |
| Net weight                          | 0.272 kg                                |
| Depth                               | 173 mm                                  |
| Length                              | 173 mm                                  |
| Width                               | 90 mm                                   |
| Height                              | 90 mm                                   |
| Targeted country                    | Australia                               |
|                                     |   |

#### Environment

| IP degree of protection               | IP66 conforming to AS 60529 |
|---------------------------------------|-----------------------------|
| Ambient air temperature for operation | -2575 °C                    |
| Standards                             | AS/NZS 3120                 |

## Packing Units

| Package 1 Weight | 0.320 kg   |  |
|------------------|------------|--|
| Package 1 Height | 80.000 mm  |  |
| Package 1 width  | 95.000 mm  |  |
| Package 1 Length | 175.000 mm |  |

### Offer Sustainability

| Sustainable offer status   | Green Premium product           |  |
|----------------------------|---------------------------------|--|
| EU RoHS Directive          | Compliant E EU RoHS Declaration |  |
| Mercury free               | Yes                             |  |
| RoHS exemption information | ₽¥Yes                           |  |
| China RoHS Regulation      | ☑ China RoHS Declaration        |  |
| Environmental Disclosure   | Product Environmental Profile   |  |

Life Is On