# 56SW420CO-GY

56 Series - Switch - Change Over - 4 Pole - 20A - 500V - grey





#### Main

| IVIAIII                   |                                     |
|---------------------------|-------------------------------------|
| Range of product          | Series 56                           |
| Range                     | Clipsal - 56 Series                 |
| Product brand             | Clipsal                             |
| Product or component type | Switch                              |
| Device presentation       | Basic element with full cover plate |
| Device application        | Control                             |
| Colour                    | Cover: grey                         |
| Handle colour             | Grey                                |
| Suitability for isolation | Yes                                 |

#### Complementary

| Switch function                | 4-pole             |
|--------------------------------|--------------------|
| Poles description              | 4P                 |
| Control type                   | Rotary knob        |
| Number of poles                | 4                  |
| Device mounting                | Surface            |
| Fixing mode                    | By screws          |
| Material                       | PC (polycarbonate) |
| Tightening torque              | 0.8 N.m            |
| Local signalling               | without            |
| [Ue] rated operational voltage | 500 V AC 50 Hz     |
| Rated current                  | 20 A               |
| Breaking capacity              | 20 kA              |
| Rotary handle padlocking       | 2 padlocks 8 mm    |
| Marking location               | Marking on surface |
| Height                         | 107 mm             |
| Width                          | 101 mm             |
| Depth                          | 124 mm             |
| Net weight                     | 0.64 kg            |
| Targeted country               | Australia          |
|                                |                    |

#### **Environment**

| Ambient air temperature for operation | -2575 °C                    |
|---------------------------------------|-----------------------------|
| IP degree of protection               | IP66 conforming to AS 60529 |
| Standards                             | AS/NZS 3133                 |

### **Packing Units**

| Unit Type of Package 1       | PCE    |  |
|------------------------------|--------|--|
| Number of Units in Package 1 | 1      |  |
| Package 1 Weight             | 664 g  |  |
| Package 1 Height             | 127 mm |  |
| Package 1 width              | 104 mm |  |
| Package 1 Length             | 107 mm |  |

## Offer Sustainability

| Sustainable offer status   | Green Premium product          |  |
|----------------------------|--------------------------------|--|
| EU RoHS Directive          | Compliant EEU RoHS Declaration |  |
| Mercury free               | Yes                            |  |
| RoHS exemption information | €Yes                           |  |
| China RoHS Regulation      | China RoHS Declaration         |  |
| Environmental Disclosure   | Product Environmental Profile  |  |