

Switched Socket, Easy56, 3 Pin, 15A, 250V

EY56C315

Main

Product name	Easy56
Product or component type	Switch and socket-outlet
Device short name	EY56C315
Plug, socket category	Low voltage
Poles description	1P + N + E
Control type	Rotary knob
Rotary handle padlocking	2 padlocks 8 mm
Network type	AC
Outlet standard deviation	Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	15 A
Pin number	3 pins
Shape of pin	Flat
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Protection type	Without protection
Material	Polycarbonate
Contacts material	Pins: phosphor bronze
Connections - terminals	Screw terminals
Cable cross section	1.56 mm²
Cable entry number	2 x M25 1 x M32
Net weight	0.82 kg
Height	203 mm
Width	101 mm
Depth	101 mm
Colour	Body: grey (RAL 7035) Rotary handle: dark grey

Environment

Standards	AS/NZS 3112 AS/NZS 3133	
Quality labels	RCM	
IP degree of protection	IP66 conforming to AS 60529	
Ambient air temperature for operation	-2575 °C	
Ambient air temperature for storage	-2575 °C	

Packing Units

PCE
1
11.4 cm
10.4 cm
20.7 cm
861 g
CAR
12
21.8 cm
35.3 cm
45 cm
10532 g
PAL
240
100 cm
80 cm
120 cm
224640 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture		
Take-back	No	