Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Socket Connector, Easy56, 15A, 250V

EY56CSC315

Main

Product or component type	Connector
Accessory / separate part category	Connection accessory
Product compatibility	Plug Easy56 EY56P315
Plug, socket category	Low voltage
Poles description	1P + N + E
Pin number	3 pins
Shape of pin	Flat
Network type	AC
Outlet standard deviation	Australian/New Zealand

Complementary

Plug, socket, control station shape	Straight	
[In] rated current	15 A	
[Ue] rated operational voltage	230/240 V	
Network frequency	50 Hz	
Material	Polycarbonate: housing	
Contacts material	Sleeves: brass	
Connections - terminals	Screw terminals	
Cable cross section	1.5 mm²	
Wire stripping length	1234 mm	
Cable outer diameter	7.410.6 mm	
cable entry	Cable gland	
Thread type	M20	
Net weight	0.107 kg	
Height	65 mm	
Width	65 mm	
Depth	105 mm	
Colour	Plug: orange (RAL 2004) Body: clear	

Environment

Standards AS/NZS 3120

Quality labels	RCM	
IP degree of protection	IP66 conforming to AS 60529	
Ambient air temperature for operation	-2575 °C	
Ambient air temperature for storage	-2575 °C	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	6.2 cm
Package 1 Length	10.8 cm
Package 1 Weight	123 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Total lifecycle Carbon footprint	4
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No