

# Socket, Easy56, 4 Pin, 20A, 500V

EY56SO420

### Main

Product name	Easy56
Product or component type	Socket-outlet
Device short name	EY56SO420
Plug, socket category	Low voltage
Poles description	3P + E
Network type	AC
Outlet standard deviation	Australian/New Zealand

## Complementary

Mounting mode	Surface mounted	
Plug, socket, control station shape	Straight	
[In] rated current	20 A	
Pin number	4 pins	
Shape of pin	Tubular	
[Ue] rated operational voltage	500 V	
Network frequency	50 Hz	
Material	Polycarbonate: cover	
Contacts material	Pins: brass	
Connections - terminals	Screw terminals 2.56 mm² rigid or stranded cable	
Wire stripping length	16 mm	
Net weight	0.471 kg	
Height	101 mm	
Width	101 mm	
Depth	101 mm	
Colour	Grey (RAL 7035)	

### **Environment**

Standards	AS/NZS 3123	
IP degree of protection	IP66 conforming to AS 60529	
Ambient air temperature for operation	-2575 °C	
Ambient air temperature for storage	-2575 °C	

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.2 cm
Package 1 Width	10.5 cm
Package 1 Length	10.5 cm
Package 1 Weight	522.5 g



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Total lifecycle Carbon footprint	3
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No