

## Product data sheet

### Characteristics

# CLITPDB2EM

LED batten diffused, Clipsal, 40 W, 4000 K, 4000 lm, 1200mm, Emergency, white



### Main

Range	Clipsal
Product name	TPDB Series
Product or component type	Batten light
Device application	Lighting
Battery type	LiFePO4

### Complementary

Type of installation	Indoor/outdoor
Operational power in W	40 W
Light source	LED
[Ue] rated operational voltage	240 V AC 50 Hz
Luminous flux	4000 lm
Bulb lifespan	30000 h
Colour	White
Colour temperature	4000 K
Autonomy	3 h
Charging time	16 h
Control type	Test button
Supply	Non-maintained
Device mounting	Surface
Mounting mode	Ceiling
IP degree of protection	IP20
Electrical insulation class	Class I
Length	1170 mm
Width	72.5 mm
Height	72 mm
Shape	Rectangular
Distance between centers	1170 mm
Net weight	2.2 kg

### Environment

Colour rendering index	R <sub>a</sub> =80
Ambient air temperature for operation	-10...45 °C
Relative humidity	10...95 %
Targeted country	Australia

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.4 kg
Package 1 Height	7.5 cm
Package 1 width	7.7 cm
Package 1 Length	121.6 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Weight	10.0 kg
Package 2 Height	17 cm
Package 2 width	17.4 cm
Package 2 Length	123 cm