

Product data sheet

Characteristics

CLITPFLT20SEN

LED Floodlight, Clipsal - Lighting, 20W, 4000K, IP65, PIR sensor, black



Main

Range	Clipsal
Product or component type	Floodlight
Device application	Lighting
Main colour tint	Black
Colour tint	Black

Complementary

Type of installation	Outdoor
Device mounting	Surface Ceiling
Total system power	20 W
Light source	LED
[Ue] rated operational voltage	230 V AC 50 Hz
Luminous flux	0...95 % RH non-condensing: 2100 lm
Colour rendering index	R _a =80
Bulb lifespan	50000 h
Colour temperature	4000 K
Beam angle	110 °
Height	Outdoor: 166 mm
Width	122 mm
Depth	29 mm
Net weight	0.68 kg
Cable length	0.6 m

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP65
Ambient air temperature for operation	-20...40 °C
Relative humidity	10...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6 cm
Package 1 Width	14.7 cm
Package 1 Length	21.7 cm
Package 1 Weight	621 g

Unit Type of Package 2	CAR
Number of Units in Package 2	16
Package 2 Height	30.5 cm
Package 2 Width	23 cm
Package 2 Length	55.5 cm
Package 2 Weight	10.654 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	3-Years
----------	---------