


Product datasheet

Specifications



Distribution board kit, MAX9 PRO, with 3Phase Comb busbar 15 ways

MX9DBKCB

Main

Range	MAX9
Product or component type	Kit
Accessory / separate part category	Enclosure accessory
Total number of 18 mm modules	15

Complementary

Number of ways	Outgoer: 15 ways 3 L
Poles configuration for 1 way	Outgoer: 3P
Connection pitch	Outgoer: 18 mm
Insulation	Insulated
Device presentation	Cuttable
Provided equipment	12 pieces tooth covers 1 neutral link 3 connecting cables with lug
[Ie] rated operational current	100 A
[Ue] rated operational voltage	415 V AC
[Ui] rated insulation voltage	500 V conforming to AS/NZS 61439-1
[Uimp] rated impulse withstand voltage	4 kV
Mounting mode	Horizontal
Mounting location	Top
Colour	White (RAL 9003)
Range compatibility	MAX9 PRO distribution board

Environment

Standards	AS/NZS 61439.3
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.2 cm
Package 1 Width	8.2 cm
Package 1 Length	21.5 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Weight	1 kg
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	16.75 kg
Unit Type of Package 3	P12
Number of Units in Package 3	288
Package 3 Height	105 cm
Package 3 Width	114 cm
Package 3 Length	114 cm
Package 3 Weight	310 kg

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	67
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACH Regulation	REACH Declaration
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Use Again

 Repack and remanufacture	
End of life manual availability	No need of specific recycling operations
Take-back	No