Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



## Switchboard Enclosure, MAX9, Type 1, 1 Row, 11 Ways, Surface Mounted

MX9E1111S

#### Main

| Range                           | MAX9  |  |
|---------------------------------|---|--|
| Product brand                   | Clipsal   |  |
| Product or component type       | Enclosure   |  |
| Device application              | Distribution  |  |
| Number of 18 mm modules per row | 11  |  |
| Provided equipment              | Earthing bar<br>Neutral bar<br>Circuit identification label<br>Blanking plate |  |
| Colour                          | White electric (RAL 9003)   |  |
| Door type                       | tinted transparent door - upwards   |  |

## Complementary

| Enclosure mounting             | Surface                              |  |
|--------------------------------|--------------------------------------|--|
| Number of horizontal rows      | 1                                    |  |
| [Ue] rated operational voltage | 240/415 V AC                         |  |
| [In] rated current             | 100 A                                |  |
| [Ui] rated insulation voltage  | 500 V                                |  |
| Number of ways                 | 11 ways                              |  |
| Cable entry                    | knock-out cable entries              |  |
| Type of rail                   | DIN                                  |  |
| Enclosure material             | Housing: plastic Front face: plastic |  |
| Width                          | 231 mm                               |  |
| Height                         | 210 mm                               |  |
| Depth                          | 113 mm                               |  |

### **Environment**

| Standards               | AS/NZS 61439-3<br>AS/NZS 3000 |
|-------------------------|-------------------------------|
| Fire resistance         | 650 °C                        |
| IP degree of protection | IP30                          |
| IK degree of protection | IK05                          |

# **Packing Units**

| 9                            |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 12.4 cm  |
| Package 1 Width              | 21.0 cm  |
| Package 1 Length             | 23.5 cm  |
| Package 1 Weight             | 1.434 kg |
| Unit Type of Package 2       | CAR      |
| Number of Units in Package 2 | 6        |
| Package 2 Height             | 24.5 cm  |
| Package 2 Width              | 39.0 cm  |
| Package 2 Length             | 44.5 cm  |
| Package 2 Weight             | 9.304 kg |

# **Contractual warranty**

Warranty 7-year



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

| ☑ Environmental footprint        |                               |
|----------------------------------|-------------------------------|
| Total lifecycle Carbon footprint | 7                             |
| Environmental Disclosure         | Product Environmental Profile |

#### **Use Better**

| Packaging made with recycled cardboard | Yes  |
|--|--|
| Packaging without single use plastic   | Yes  |
| EU RoHS Directive                      | Pro-active compliance (Product out of EU RoHS legal scope) |
| REACh Regulation                       | REACh Declaration  |

#### **Use Again**

| ○ Repack and remanufacture      |  |
|---------------------------------|--|
| End of life manual availability | No need of specific recycling operations |
| Take-back                       | No                                       |

Image of product / Alternate images

**Alternative** 



