

Product data sheet

Characteristics

P3042A-BK

Pro Series, 2 switches, architrave, vertical, 1 or 2 way, 10 AX, Black



Main

Range	Pro Series
Product or component type	Switch
Colour tint	Black
Type of packing	Polybag
Quantity per set	Set of 20

Complementary

Device presentation	Complete product
Control type	Rocker
Device mounting	Wall
Installation direction	Vertical
Switch function	1-pole 1/2-way
Number of rocker	2
Rated current	20 A/16 AX
[Ue] rated operational voltage	250 V
Material	PC (polycarbonate) PP (polypropylene) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene)
Fixing mode	By screws
Surface finish	Glossy
Surface treatment	Untreated
Connections - terminals	Screw terminal
Clamping connection capacity	1 x 1.5...4 x 1.5 mm ² for rigid or stranded cable(s) 3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s)
Height	113 mm
Width	38 mm
Depth	40 mm
Net weight	0.063 kg

Environment

Ambient air temperature for operation	0...45 °C
Relative humidity	10...95 %
Product certifications	RCM

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	92.33 g
Package 1 Height	3.8 cm
Package 1 width	7.8 cm
Package 1 Length	11.6 cm