

Product data sheet

Characteristics

P3045VA-XW

Pro Series, 5 switches, vertical, 1 or 2 way, 20 A / 16 AX, White



Main

| | |
|---------------------------|------------|
| Range | Pro Series |
| Product or component type | Switch |
| Device application | Lighting |
| Colour tint | White |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |

Complementary

| | |
|--------------------------------|--|
| Device presentation | Complete product |
| Control type | Rocker |
| Device mounting | Wall |
| Installation direction | Vertical |
| Switch function | 1-pole 1/2-way |
| Number of rocker | 5 |
| Rated current | 20 A/16 AX |
| [Ue] rated operational voltage | 250 V |
| Material | PC (polycarbonate) PP (polypropylene) ABS (acrylonitrile butadiene-styrene) POM (polyoxymethylene) |
| Fixing mode | By screws |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| Connections - terminals | Screw terminal |
| Clamping connection capacity | 1 x 1.5...4 x 1.5 mm ² for rigid or stranded cable(s) 3 x 2.5 mm ² for stranded cable(s) 1 x 4 mm ² for stranded cable(s) |
| Height | 116 mm |
| Width | 78 mm |
| Depth | 38 mm |
| Net weight | 0.108 kg |

Environment

| | |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Product certifications | RCM |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.