

Product data sheet

Characteristics

P432

PLUG TOP ALUM 32A 500V 4R PINS



Main

| | |
|------------------|-------------------|
| Range of product | Series P Wilco |
| Product brand | Clipsal |

Complementary


| | |
|-------------------------------------|---|
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 500 V 50/60 Hz conforming to EN 60309-2 |
| Material | Aluminium |
| Connections - terminals | Screw terminal |
| Plug, socket, control station shape | Straight |
| Pin arrangement | N |
| Duration | 7 h |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 650.0 g |
| Package 1 Height | 8.1 cm |
| Package 1 width | 8.5 cm |
| Package 1 Length | 13.5 cm |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 1080 |
| Package 2 Weight | 811.6 kg |
| Package 2 Height | 114 cm |
| Package 2 width | 116.5 cm |
| Package 2 Length | 116.5 cm |
| Unit Type of Package 3 | CAR |
| Number of Units in Package 3 | 20 |
| Package 3 Weight | 14.4 kg |
| Package 3 Height | 16.5 cm |
| Package 3 width | 37 cm |
| Package 3 Length | 37 cm |

Offer Sustainability

EU RoHS Directive

Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS
Declaration