

Product data sheet Characteristics

CLP501902 Wiser Hub





Main	
Range	Wiser
Product or component type	Zigbee/IP gateway
Device application	Zigbee/IP network interface

Complementary

Colour	White	
Communication network type	Ethernet conforming to IEEE 802.3 WLAN - 2.4 GHz conforming to IEEE 802.11 b/g/n ZigBee - 2.4 GHz conforming to IEEE 802.15.4	
Port Ethernet	10/100BASE	
Connector type	Connector(S)1 x micro USB port female for adaptor Connector(s)1 x 2-pin terminal block for 12 V DC power supply	
Electrical connection	Cable, 0.251.5 mm² (terminal)	
[Us] rated supply voltage	5 V DC, <1 A 12 V DC, <0.5 A	
Realtime clock	With RTC-battery set	
Local signalling	Indicator: 3 LEDs (white)	
Width	86 mm	
Height	86 mm	
Depth	34 mm	

Environment

Littlioillioil	
Ambient air temperature for operation	040 °C
Relative humidity	1090 %
Environmental characteristic	Indoor use
IP degree of protection	IP20
Standards	EN 62368-1 IEC 62368-1
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	357 g	
Package 1 Height	6.9 cm	
Package 1 width	13.4 cm	
Package 1 Length	18.7 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant [™] EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	☑ Product Environmental Profile
Circularity Profile	End Of Life Information

Life Is On