

Product data sheet Characteristics

CLP591011

Wiser window/door sensor





Main Product brand Clipsal Range compatibility Wiser Wiser hub Range Wiser Product name Wiser window/door sensor Product or component Sensor

White

Battery / CR2450

Complementary

- Compression y		
Device application	Building automation systems	
[Ue] rated operational voltage	3 V	
Battery life	5 year(s)	
Communication port protocol	Zigbee at 2.4 GHz conforming to IEEE 802.15.4	
Device composition	Sensor 50 mm x 33 mm x 16.3 mm Magnet 50 mm x 9 mm x 9 mm	
Alive signal	48/day	
Magnet gap	< 18 mm on wood and plastic surface < 10 mm on metallic surface	
Standards	IEC 60669-2-5 EN 60669-2-5	
Product certifications	CE Zigbee 3.0	

Colour tint

Supply

Environment

211 Office Control of		
IP degree of protection	IP20	
Relative humidity	1095 %	
Ambient air temperature for operation	-1050 °C	
Operating altitude	<= 2000 m	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	84 g	
Package 1 Height	7.5 cm	
Package 1 width	5.2 cm	
Package 1 Length	7.5 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant [™] EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	☑ Product Environmental Profile
Circularity Profile	End Of Life Information

Life Is On