

Product data sheet

Characteristics

RMXPC1

Connector, Resi MAX, 1P+N, set of 4



Main

Range	Resi MAX
Product or component type	Connector
Accessory / separate part category	Connection accessory
Quantity per set	Set of 4
Colour	White (RAL 9003)

Complementary

Poles description	1P + N
Mounting mode	Horizontal
[Ie] rated operational current	63 A at 40 °C
Connections - terminals	Screw clamp terminals 1...35 mm ² rigid
Tightening torque	4 N.m

Packing Units

Package 1 Weight	0.048 kg
Package 1 Height	0.200 dm
Package 1 width	0.800 dm
Package 1 Length	0.700 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.