

Product data sheet

Characteristics

RMXPH312

comb busbar, Resi MAX, 3P+N, 12 modules, 80A



Main

| | |
|------------------------------------|--|
| Product brand | Clipsal |
| Range | Resi MAX |
| Product or component type | Comb busbar |
| Accessory / separate part category | Connection accessory |
| Poles description | 3P + N |
| Number of ways | 12 ways N + L tooth connector(s) with 9 mm pitch |
| Distance between way | 18 mm |
| Length in 18 mm modules | 12 |

Complementary

| | |
|--|------------------------------------|
| Insulation | Insulated |
| Device presentation | Cuttable |
| [Ie] rated operational current | 80 A at 40 °C |
| [Ue] rated operational voltage | 230 V AC Ph/N 400 V AC Ph/Ph |
| [Ui] rated insulation voltage | 500 V AC conforming to IEC 61439-1 |
| [Uimp] rated impulse withstand voltage | 6 kV |
| Mounting mode | Horizontal |
| Mounting location | Bottom on tunnel type terminals |
| 9 mm pitches | 24 |
| Width | 216 mm |
| Colour | White (RAL 9003) |

Environment

| | |
|------------------|---|
| Standards | IEC 61439-1 IEC 60947-7-1 |
| Fire resistance | 960 °C (30 s) conforming to IEC 60695-2-1 |
| Pollution degree | 3 conforming to IEC 60947-7-1 |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 0.150 kg |
| Package 1 Height | 0.580 dm |
| Package 1 width | 0.860 dm |
| Package 1 Length | 2.330 dm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |