

Product data sheet Characteristics

WMC432 SWITCHED SOCKET 32A 500V 4R SIZE 2 CAST ALUMINIUM MATERIAL





Main Range of product Wilco Series A Product brand Clipsal Device application Power supply

Complementary

Number of poles	4	
Number of modules	3	
Number of power socket outlets	1 protective cover	
[In] rated current	32 A	_
[Ue] rated operational voltage	500 V AC	
Device mounting	Surface	_
Material	Cast aluminium: housing	
Depth	120 mm	
Width	115 mm	_
Height	258 mm	_

Packing Units

PCE	
1	
2.22 kg	
10.3 cm	
11.8 cm	
24.3 cm	
	1 2.22 kg 10.3 cm 11.8 cm

Offer Sustainability

☑ REACh Declaration
E REACT Declaration
Compliant EEU RoHS Declaration
Yes
₫Yes
China RoHS Declaration
Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or infability of these products for specific user applications. It is the doubt of any substitute for and is not to be used for determining suitability or infability of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or substitaires shall be responsible or liable for misuse of the information contained herein.