

Product data sheet

Characteristics

WS226SSR/3-RG

SWITCH SUNSET 3 WIRE 10A X 12 HOURS.

WS226SSR/3 REPLACES WDL10.



Main

Range of product	Weathershield
Product brand	Clipsal
Device presentation	Basic element

Complementary

Fixing mode	By screws
Local signalling	without
[Ue] rated operational voltage	240 V AC
Rated current	10 A 10 AX, fluorescent lamp
Marking	Without marking

Environment

Standards	AS/NZS 3133 AS/NZS 3100 IEC 60669-2-1
-----------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	0.26 kg
Package 1 Height	8 cm
Package 1 width	35.2 cm
Package 1 Length	9.4 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	18
Package 2 Weight	5.24 kg
Package 2 Height	23.7 cm
Package 2 width	20.3 cm
Package 2 Length	30 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information