



Sm.distr, golf, surface, 12M, wh door

VS112PT

#### Architecture

Fixing mode	surface-mounting
-------------	------------------

#### Functions

With a pipe-in lead	yes
---------------------	-----

#### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

#### Main electrical features

Nominal voltage	400 V
-----------------	-------

#### Cover, door

Cover type	Closed (plain)
------------	----------------

Transparent cover or door	no
---------------------------	----

Cover type	Door
------------	------

Door locking	without
--------------	---------

Type of door closing	Latch
----------------------	-------

Door leave	single
------------	--------

Door quantity	1
---------------	---

Identification od protection index	40
------------------------------------	----

Interlockable	no
---------------	----

#### Materials

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Colour	white
--------	-------

Colour	pure white
--------	------------

Material	plastic
----------	---------

Enclosure material	plastic
--------------------	---------

Type of surface treatment	untreated
---------------------------	-----------

#### Dimensions

Depth of installed product	98,5 mm
----------------------------	---------

Internal depth	98,5 mm
----------------	---------

Height of installed product	251,5 mm
-----------------------------	----------

Width of installed product	281,5 mm
----------------------------	----------

Width in division units	12
-------------------------	----

#### Installation, mounting

Suitable for outdoor use	no
--------------------------	----

#### Accessories included

Mounting plate included	no
With lock	no

#### Equipment

Number of rows	1
Quantity of section in width	1
Can be accessorized	yes
Quantity of rails	1

#### Standards

GWT Glow wire test	650 °C
--------------------	--------

#### Safety

Protection class	isol.class II
Protection index IP	IP40
IK protection code against mechanical impacts	IK07
Halogen free	yes
Impact strength	IK07
Ultraviolet resistant	no

#### Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------