



## PLUTO 100

Australian approved constant voltage LED driver IP67

### Application

An ideal choice for LED strips, LED Neon or exterior lighting requirements

### Design Specifications

- SELV and EMC compliant
- Safe no load operation, power factor 0.9, non-dimmable
- Overload and short circuit protection
- 1.2m flex and plug fitted for easy installation, output (secondary) end is provided with rubber fly leads
- Durable metal casing IP67
- Minimum load 10 watt




### Technical Specification

Model No.	Input Voltage (V/AC)	Output Voltage (V/DC)	Frequency (Hz)	Power (W)	Power Factor	Dim (mm)
PLUTO 100/12V	240	12	50	100	0.9	262(L) x 40(W) x 23(H)
PLUTO 100/24V	240	24	50	100	0.9	262(L) x 40(W) x 23(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

### Dimensions



# THE SFI SYSTEM ELIMINATES LED FLICKERING.

**DIMMABLE  
CONTROL WITH  
SFI FLICKER  
CONTROL  
TECHNOLOGY**  
when paired with  
**SAL SFI downlights**



**DIM with  
FLICKER  
CONTROL**

For related  
products  
please  
scan me

