



## PLUTO 250FC - 24V 250W

Australian approved constant voltage flickerCONTROL LED power supply, IP67

### Application

An ideal choice for LED strips, LED Neon or inground lighting requirements

### Design Specifications

- SELV and EMC compliant
- Safe no load operation, power factor 0.95
- Overload and short circuit protection, flickerCONTROLLED performance
- 1.2 m flex and plug fitted for easy installation, output (secondary) end is provided with rubber fly leads
- Durable metal casing IP67
- Electrical class I, Do Not Cover.  
Minimum load, 250/24V 1 watt, Max. LED Driver Number on MCB C type 16A (for driver >100W) = 15



### Performance

- Dimmable - **NO**



### Technical Specification

Product	Model No.	Input Voltage (V/AC)	Frequency (Hz)	Output Voltage (V/DC)	Power (W)	Power Factor
	PLUTO 250/24V/FC	240	50	24	250	0.95
Model No.	Dimmable	Dim (mm)				
PLUTO 250/24V/FC	NO	227(L) x 61(W) x 34(H)				

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".