



PIXIE CONTACT SENSORS

Accessories for PIXIE smart products

Application

Perfect for windows, doors and gates.

Design Specifications

- **CSF21BTP** - concealed contact sensor suitable for timber doors and windows, flush mounted, Ø 11mm, depth 16.8mm - wire length 500mm
- **CSM41BTP** - suitable for metal doors and gates, surface mounted- wire length 500mm
- **CSR41BTP** - suitable for roller doors, surface mounted - wire length 650mm
- For wiring diagrams, please refer to PC206GD/R/BTAM or PC100CS/R/BTAM




Technical Specification

Product	Model No.	Body Colour
	CSF21BTP	WHITE
	CSM41BTP	GREY
	CSR41BTP	GREY


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

FLUSH MOUNT CONTACT SENSOR CSF21BTP



METAL DOOR CONTACT SENSOR CSM41BTP



ROLLER DOOR CONTACT SENSOR CSR41BTP

