



Identify people & vehicles.

Professional AI Series: Fixed AI turret dome cameras in 6.0MP & 8.0MP

The Professional AI Series identifies people & vehicles using machine learning, to reduce false motion detection alerts and provide meaningful video event notifications in real-time. When used in conjunction with a VIP Vision NVR, person and vehicle events can be isolated in footage playback to improve surveillance efficiency.

- Stream up to 8.0MP (3840 x 2160) at 20fps
- H.265 encoding for efficient storage & streaming
- Up to 50m infrared range; true day/night (auto ICR)
- Back/highlight compensation & true WDR (120dB)
- MicroSD slot for recording at the edge up to 256GB
- Intelligent AI detection to identify people & vehicles
- Smart Motion Detection (SMD+) & Perimeter Protection to prevent false alarms, using VIP Vision NVRs
- 3D digital noise reduction & auto white balance
- IP67 weather rated housing for outdoor use



Record at 4K Ultra HD Resolution



Smart Person & Vehicle Detection



Superb Low Light Performance

Specifications		6.0MP Fixed AI Turret Dome	8.0MP Fixed AI Turret Dome	
Ordering Information		VSIPP-6DIRG-I : 6.0MP Standard	VSIPP-8DIRG-I : 8.0MP Standard	
Camera	Image Sensor	1/2.7" 6.0MP Progressive Scan CMOS	1/2.8" 8.0MP Progressive Scan CMOS	
	Effective Pixels	3072 x 1728	3840 (H) x 2160 (V)	
	RAM / ROM	512MB / 128MB		
	Min Illumination	0.005 Lux/F1.6 (Colour)	0.007 Lux/F1.4 (Color)	
	S/N Ratio	>56dB		
	Infrared System	2 x Infrared LED, 50m range, Auto/manual on/off control	2 x Infrared LED, 30m range, Auto/manual on/off control	
Lens	Lens / Iris	2.8mm F1.6 Fixed Lens	2.8mm F1.4 Fixed Lens	
	Field of View	Horizontal: 99°, Vertical: 53°	Horizontal: 108°, Vertical: 58°	
	Focus	Auto Focus / 0.9m Min. Focus Distance	Fixed / 1.4m Min. Focus	
DORI	Detect (25px/m)	56m	85m	
	Observe (63px/m)	22m	34m	
	Recognise (125px/m)	11m	17m	
	Identify (250px/m)	6m	9m	
Video	Resolution	6.0MP (3072 x 1728) to CIF (352 x 288)	8.0MP (3840 x 2160) to CIF (352 x 288)	
	Frame Rate	Main	6.0MP (1 ~ 20fps) / 4.0MP (1 ~ 25fps)	8.0MP (1 ~ 20fps)
		Sub	D1 (1 ~ 25fps)	
		Third	1080p (1 ~ 25fps)	
	Video Compression	H.265+ / H.265 / H.264+ / H.264 / H.264B / MJPEG		
	Bit Rate	H.265: 19 ~ 8192Kbps / H.264: 32 ~ 8192Kbps	H.265: 3 ~ 8192Kbps / H.264: 3 ~ 8192Kbps	
	Bit Rate Control	Constant bit rate (CBR) / Variable bit rate (VBR)		
	Day/Night	Auto (ICR) / Color / B&W		
	Lighting Compensation	BLC / HLC / WDR (120dB)		
	White Balance	Auto / Natural / Street Lamp / Outdoor / Manual / Regional Custom		
Gain Control	Auto / Manual			
Noise Reduction	3D DNR			
Picture Control	Mirror / Flip (0°, 90°, 180°, 270°) (Support 90°/270° with 2.0MP resolution)			
IVS	Video Functions	Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		
	AI Functions	Smart Motion Detection (SMD+) : People and vehicle detection using motion detection Perimeter Protection : People and vehicle detection using tripwire or intrusion rules		
	Intelligent search	Search people or vehicle detection events (SMD+, Perimeter Protection)		
Network	Ethernet	RJ-45 (10/100Base-T)		
	Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP		
	Streaming Method	Unicast / Multicast		
	Max. User Access	20 Users		
Interface	Video Interface	N/A		
	Audio Interface	Built-in Mic / Audio Compression - G.711a; G.711Mu; G.726; AAC; G.723		
	Alarm Interface	N/A		
	RS485	N/A		
	Edge Storage	MicroSD Card (up to 256GB) / NAS / FTP / SFTP		
	Interoperability	ONVIF / P2P / CGI / Milestone / Genetec		
Environmental	Power Supply	12VDC / PoE (802.3af)		
	Power Consumption	<7.2W	<7.9W	
	Operating Conditions	-40°C ~ +60°C / ≤95% RH		
	Ingress Protection	IP67		
	Vandal Resistance	N/A		
	Housing	Metal		
	Pan/Tilt/Rotation	Pan: 0° ~ 360°, Tilt: 0° ~ 78°, Rotation: 0° ~ 360°		
	Dimensions	Ø106mm x 93.6mm		
Net Weight	0.55kg	0.53kg		

Application					
	Junction Box	Weather Shield	Wall Mount		Corner Mount
	VSBKTA130E	VSBKTA130E + VSBKTA200W	VSBKTB204W	VSBKTA106 + VSBKTB305W	VSBKTA106 + VSBKTB305W + VSBKTA151
	Corner Mount	Pole Mount			Ceiling Mount
	VSBKTB204W + VSBKTA151	VSBKTA106 + VSBKTB305W + VSBKTA150	VSBKTA130E + VSBKTA152E	VSBKTB204W + VSBKTA152E	VSBKTA106 + VSBKTB220C (+ VSBKTA117 optional extension)

Your local VIP Vision™ IP solutions professional: